

INSTALLATION INSTRUCTION

LED CEILING LIGHT
CCT SELECT WITH BUILT-IN SWITCH



2 YEARS
WARRANTY*

TECHNICAL SPECIFICATIONS:

Model	Watts	Input Voltage	Lumen	Dimension	Color Temperature	Operation Temperature
VT-8412	12W	AC:175-265V ,50/60Hz	720LM	Ø255x55mm	3000K-4000K-6400K	-20°C to +45 °C
VT-8418	18W	AC:175-265V ,50/60Hz	1080LM	Ø310x55mm	3000K-4000K-6400K	-20°C to +45 °C
VT-8424	24W	AC:175-265V ,50/60Hz	1440LM	Ø350x55mm	3000K-4000K-6400K	-20°C to +45 °C
VT-8436	36W	AC:175-265V ,50/60Hz	2160LM	Ø480x65mm	3000K-4000K-6400K	-20°C to +45 °C

WARNING!

1. Please make sure to turn off the power before starting the installation.
2. The light source of this luminaire is not replaceable; when the light source reaches its end of life the whole luminaire shall be replaced.
3. Install only by certified Electrician.



This marking indicates that this product should not be disposed of with other household wastes.



Caution, risk of electric shock.

USAGE & MAINTENANCE:

Any maintenance work must be performed when the power supply is cut off and the product has cooled down. Clean only with soft and dry cloth. Do not use chemical detergents. Do not cover the product. Ensure free air access. Product may heat up to a higher temperature. **ATTENTION!** Do not look directly at LED light beam. Product can only be supplied by rated voltage or voltage within the range provided. It's forbidden to use the product with damaged protective cover. Product must not be used unfavorable conditions, e.g. dust, water, moisture, vibrations, explosive air atmosphere, fumes, or chemical fumes, etc. In the area of strong electromagnetic interference, the functioning of the product may be disrupted.

INSTALLATION INSTRUCTION

